

RER70F II SERIES

Static load: 8000 Kg

Motors: 4 poles 50Hz



RATIO	SHEAVE	SPEED	HP14	HP16	HP18	HP20	HP22	HP25
	DIA/mm	m/sec	Kg	Kg	Kg	Kg	Kg	Kg
65:1	520	0.57-0.63	1300					
	600	0.66-0.72	1100					
	650	0.71-0.78	1000					
	700	0.77-0.84	920					
55:1	520	0.67-0.74	1200	1450				
	600	0.78-0.86	1050	1280				
	650	0.84-0.93	950	1170				
	700	0.90-1.00	900	1080				
48:1	520	0.77-0.85	1100	1340	1500			
	600	0.89-0.98	960	1140	1300			
	650	0.96-1.06	880	1040	1200			
	700	1.04-1.14	800	960	1100			
38:1	520	0.97-1.07	960	1100	1260	1450	1500	1600
	600	1.12-1.24	830	960	1060	1250	1300	1500
	650	1.22-1.34	760	880	1000	1150	1200	1400
	700	1.31-1.45	720	800	920	1060	1100	1300
54:2	520	1.37-1.51		920	1040	1180	1250	1400
	600	1.58-1.74		780	900	1020	1080	1250
	650	1.71-1.89		720	820	940	980	1100
	700	1.84-2.03		660	760	860	920	1060